

## Compare products



### Specification

	<b>Linear LED luminaire</b>	<b>Linear LED luminaire</b>	<b>Linear LED luminaire</b>	<b>Linear LED luminaire</b>
	<b>ALD-SL-NW-MAT-B-NT</b>	<b>ALD-SL-WW-MAT-B-NT</b>	<b>ALD-SL-NW-MPR-B-NT</b>	<b>ALD-SL-WW-MPR-B-NT</b>
	Product code: 34164	Product code: 34166	Product code: 34168	Product code: 34170
Colour temperature	white	Warm white	white	Warm white
Number of on/off cycles	≥30000	≥30000	≥30000	≥30000
Luminous efficiency of the lamp [lm/W]	130	115	120	105
IP class	20	20	20	20
Colour temperature [K]	4000	3000	4000	3000
Service life [h]	50000	50000	50000	50000
Colour-rendering index Ra	80	80	80	80
Lamp-heating time [s]	≤1	≤1	≤1	≤1
Lamp-ignition time [s]	≤0,5	≤0,5	≤0,5	≤0,5
Rated frequency [Hz]	50	50	50	50
Length [mm]	580	580	580	580
Colour uniformity [SDCM]	≤3	≤3	≤3	≤3
Lighting angle [°]	X85/Y95	X85/Y95	X75/Y90	X75/Y90
Fixture lighting direction	down	down	down	down
Class of protection against electric shock	I	I	I	I
Colour	black	black	black	black
Lampshade material	plastic	plastic	plastic	plastic
Enclosure material	aluminum alloy	aluminum alloy	aluminum alloy	aluminum alloy
Place of assembly	ceiling mounted	ceiling mounted	ceiling mounted	ceiling mounted
Place of application	Indoors	Indoors	Indoors	Indoors
Minimum distance from the illuminated object	0,5m	0,5m	0,5m	0,5m
Maximum power [W]	10	10	10	10
Compatible with a dimmer	DALI	DALI	DALI	DALI
Rated voltage [V]	220-240 AC	220-240 AC	220-240 AC	220-240 AC
Diode type	LED SMD	LED SMD	LED SMD	LED SMD
Connection type	Self-clamping block	Self-clamping block	Self-clamping block	Self-clamping block
Luminous flux of the light fitting [lm]	1300	1150	1200	1050
Width [mm]	60	60	60	60
Luminous flux retention factor at the end of rated service life	L90B10	L90B10	L90B10	L90B10
Height [mm]	69	69	69	69
Range of sections of wires used [mm <sup>2</sup> ]	0,5÷2,5	0,5÷2,5	0,5÷2,5	0,5÷2,5
Ambient temperature range to which the product can be exposed	5÷25	5÷25	5÷25	5÷25
Integrated LED light source	1	1	1	1

Shade type

matt

matt

microprismatic

microprismatic